

# THIẾT BỊ CHỐNG SÉT LAN TRUYỀN

## Surger Protection Device

**HAKEL, Type 1/Type 1+2/Type 2/ Type 3/Data Series**



Date:01/05/2016

	Loại Type	Mã hàng Model	Thông số kỹ thuật Specification	Đơn giá U/P(VNĐ)
TYPE 1+2	SPC12,5	10744	1P; Uc=275 V AC Iimp (10/350) =12.5 kA; In (8/20) = 25 kA	2,980,000
	SPC12,5/1+1	10740	1P2W; Uc=275 V AC Iimp (10/350) L/N =12.5 kA; Iimp (10/350) N/PE =25 kA In (8/20) = 25 kA; Itotal (10/350) = 25 kA	4,400,000
	SPC12,5/3+0	10734	3P4W; Uc=275 V AC Iimp (10/350) =12.5 kA; Itotal (10/350) = 37.5 Ka In (8/20) = 25 kA	7,520,000
	SPC12,5/3+1 (★)	10730	3P5W; Uc=275 V AC Iimp (10/350) L/N =12.5 kA; Iimp (10/350) N/PE=50 kA In (8/20) = 25 kA	9,410,000
	SPC25	10746	1P; Uc=275 VAC Iimp (10/350) =25 kA; In (8/20) = 25kA Itotal (10/350) = 25 kA	3,930,000
	SPC25/1+1	10742	1P2W; Uc=275 VAC Iimp (10/350) L/N =25 kA;Iimp (10/350) N/PE =50 kA In (8/20) = 25 kA;Itotal (10/350) = 50 kA	5,490,000
	SPC25/3+0	10736	3P4W; Uc=275 VAC Iimp (10/350) =25 kA; In (8/20) = 25 kA;Itotal (10/350) = 75 kA	10,190,000
	SPC25/3+1	10732	3P5W; Uc=275 VAC Iimp (10/350) L/N =25 kA;Iimp (10/350) N/PE =100 kA In (8/20) = 25kA;Itotal (10/350) = 100 kA	11,750,000
TYPE 2	PIIIM 275	27004	1P; Uc=275 VAC Imax (8/20) L/N= 50 kA	950,000
	PIIIM 275 DS	27005		1,090,000
	PIIIM 275/1 + 1	27014	1P2W; Uc=275 VAC Imax (8/20) L/N= 50 kA;Iimp (10/350) N/PE =20 kA	2,000,000
	PIIIM 275 DS/1 + 1	27015		2,200,000
	PIIIM 275/3 + 0	27032	3P4W; Uc=275 VAC Imax (8/20) L/N= 50 kA	2,820,000
	PIIIM 275 DS/3 + 0	27033		3,290,000
	PIIIM 275/3 + 1 (★)	27022	3P5W; Uc=275 VAC Imax (8/20) L/N= 50 kA;Iimp (10/350) N/PE =20 kA	3,930,000
	PIIIM 275 DS/3 + 1 (★)	27023		3,517,000

(★) Hàng có sẵn

**Chú ý:**

- \* Giá trên chưa bao gồm 10% VAT
- \* Sản phẩm bảo hành 12 tháng